


1.1 Leichte Reihe DIN 3015 Teil 1, Einzelteile

1.1 Light range DIN 3015 part 1, individual parts

1.1 SERIE LEGERE selon DIN 3015 chap. 1, pièces individuelles

Abmessungen Dimensions Dimensions	Größe Size Taille	6-kt-Schraube ISO 4014 Ext. hex. bolt ISO 4014 Vis H ISO 4014 (6kt-shr.ISO4014)
M6 x 30	0	
M6 x 30	1	
M6 x 35	2	
M6 x 40	3	
M6 x 45	4	
M6 x 60	5	
M6 x 70	6	

Abmessungen Dimensions Dimensions	Größe Size Taille	Zylinder-Schraube ISO 4762 Int. hex. bolt ISO 4762 Vis CHc ISO 4762 (zyl-shr.ISO4762)
M6 x 20	0	
M6 x 20	1	
M6 x 25	2	
M6 x 30	3	
M6 x 35	4	
M6 x 50	5	
M6 x 60	6	

Abmessungen Dimensions Dimensions	Größe Size Taille	Zylinder-Schraube ISO 1207 Slotted head bolt ISO 1207 Vis tête fendue ISO 1207 (zyl-shr.ISO1207)
M6 x 20	0	
M6 x 20	1	
M6 x 25	2	
M6 x 30	3	
M6 x 35	4	
M6 x 50	5	
M6 x 60	6	

Bestellschlüssel

Order code / Code de commande

6kt-shr. ISO4014 - M6 x 30 - 8.8 - A4B

Bauart / design / série

6kt-shr. ISO4014

zyl-shr.ISO4762

zyl-shr.ISO1207

Baugröße / size / taille

ISO4014ISO4762ISO1207

M6 x 30 M6 x 20 M6 x 20

M6 x 35 M6 x 25 M6 x 25

M6 x 40 M6 x 30 M6 x 30

M6 x 45 M6 x 35 M6 x 35

M6 x 60 M6 x 50 M6 x 50

M6 x 70 M6 x 60 M6 x 60

Schraubenqualität / bolt quality / qualité de vis

ISO4014, ISO4762 = 8.8

ISO 1207 = 5.6

Oberfläche der Schraube / bolt plating / revêtement de vis

A4B

verzinkt / zinc plated / zingué