


6A

**Bride SAE
Code 62**

ISO 12151-3-S-S – SFS
6000 psi



XXXXX-XX-XX		D. Int. du tuyau				Raccordement	A mm	B mm	F mm
Référence		DN	pouce	module	mm				
46	48								
16A46-8-8	16A48-8-8	12	1/2	-8	12,7	1/2	75	51	32
16A46-12-12	16A48-12-10	20	3/4	-12	19,1	3/4	60	35	41
	16A48-12-12	25	1	-16	25,4	3/4	96	70	41
16A46-12-16	16A48-12-16	25	1	-16	25,4	3/4	99	69	41
16A46-16-16	16A48-16-16	25	1	-16	25,4	1	111	82	48
16A46-20-20		32	1-1/4	-20	31,8	1-1/4	122	84	54
	16A48-20-20	32	1-1/4	-20	31,8	1-1/4	130	83	54
	16A48-24-24	40	1-1/2	-24	38,1	1-1/2	141	103	64
	16A48-32-32	50	2	-32	50,8	2	173	124	79

Pour les dimensions et références des demi-bridés voir la section Eb.

l : i n r c 1														
441 441RH														
3 492 92S 692 692														
3	3	3	2	3	3	2	2	S	2	C	22	26	3	451
										C	C	2	C	477
													ST	4 3 8 88