

341

Hydraulic

SAE 100R9 TYPE AT



# Part Number												
	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	43 Series	
341-6	3/8	10	0.78	20	4500	31,5	5	130	0.50	0,74	•	
341-8	1/2	12,5	0.89	23	4000	28,0	7	180	0.62	0,92	•	
341-12	3/4	19	1.17	30	3000	21,0	9-1/2	240	0.92	1,37	•	
341-16	1	25	1.51	38	3000	21,0	12	300	1.28	1,90	•	
341-20	1-1/4	31,5	1.87	47	2500	17,5	16-1/2	420	1.79	2,66	•	

Application: Petroleum base hydraulic fluids and lubricating oils.

Inner Tube: Synthetic rubber.

Reinforcement: Four spiral steel wire.

Cover: Synthetic rubber, MSHA accepted.


Temperature Range: -40°F to +212°F (-40°C to +100°C).

Fittings: 43 Series - pg. B-27.

302

Hydraulic Worldwide

ISO 1436-1 TYPE 2SN / SAE 100R2 TYPE AT / EN 853 TYPE 2SN



# Part Number														
	Hose ID		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp		Field Attachable	
	inch	mm	inch	mm	psi	Mpa	inch	mm	lbs/ft	kg/m	43 Series		30 Series	
302-4	1/4	6,3	0.59	15,0	5800	40	4	100	0.26	0,39	•		•	
302-5	5/16	8	0.65	16,6	5000	35	4-1/2	115	0.28	0,42	•		•	
302-6	3/8	10	0.75	19,0	4750	33	5	130	0.37	0,55	•		•	
302-8	1/2	12,5	0.88	22,3	4000	28	7	180	0.45	0,67	•		•	
302-10	5/8	16	1.00	25,5	3600	25	8	200	0.52	0,77	•		•	
302-12	3/4	19	1.16	29,4	3100	21,5	9-1/2	240	0.67	1,00	•		•	
302-16	1	25	1.50	38,1	2400	16,5	12	300	1.00	1,49	•		•	
302-20	1-1/4	31,5	1.86	47,1	1800	12,5	16-1/2	420	1.16	1,73	•		•	
302-24	1-1/2	38	2.14	54,5	1300	9	20	500	1.44	2,14	•		•	
302-32	2	51	2.64	67,2	1150	8	25	630	1.99	2,96	•		•	

Application: Petroleum base hydraulic fluids and lubricating oils.

Inner Tube: Nitrile.

Reinforcement: Two braids steel wire.

Cover: Synthetic rubber.

Temperature Range: -40°F to +212°F (-40°C to +100°C).

Fittings: 43 Series - pg. B-27.
30 Series - pg. B-153.

471TC

Hydraulic – **TOUGH COVER**


ISO 11237-1 TYPE 2SC / EN 857 TYPE 2SC



471ST

Hydraulic – **SUPER TOUGH**

ISO 11237-1 TYPE 2SC / EN 857 TYPE 2SC



# Part Number												
	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Parkrimp	
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	43 Series	
471TC/ST-4	1/4	6,3	.51	13	5800	40,0	2	50	0.20	0,30	•	
471TC/ST-6	3/8	10	.68	17	5000	35,0	2-1/2	65	0.28	0,42	•	
471TC/ST-8	1/2	12,5	.80	20	4250	29,7	3-1/2	90	0.35	0,52	•	
471TC/ST-10	5/8	16	.94	24	3625	25,0	4	100	0.44	0,66	•	
471TC/ST-12	3/4	19	1.09	28	3125	21,5	4-3/4	120	0.58	0,86	•	
471TC/ST-16	1	25	1.40	35	2500	17,5	6	150	0.79	1,17	•	

Application: Petroleum base hydraulic fluids and lubricating oils.

Inner Tube: Synthetic rubber.

Reinforcement: Two braids steel wire.

Cover: Synthetic rubber abrasion resistant, MSHA accepted.

Temperature Range: -40°F to +212°F (-40°C to +100°C).

Fittings: 43 Series - pg. B-27.

- Field Attachable Assembly Instructions are in Section B with each Fitting Series.
- See Section C for Parkrimp Assembly Instructions.
- Temperature Range of other media listed in Section E.