


## G4MX Union femelle BSPP

Triple-Lok® cône 37° / Filetage femelle BSPP (ISO 1179-1)



| Ø ext.<br>du tube |       | Filetage<br>BSPP<br>T4 | Filetage<br>UN/UNF-2A<br>T | C1<br>mm | D<br>mm | L2<br>mm | Poids<br>(Acier)<br>gr./pièce | Triple-Lok®<br>Acier | Triple-Lok®<br>Acier inox | PN (bar) |     |
|-------------------|-------|------------------------|----------------------------|----------|---------|----------|-------------------------------|----------------------|---------------------------|----------|-----|
| mm                | in.   |                        |                            |          |         |          |                               |                      |                           | S        | SS  |
| 6                 | 1/4   | 1/8-28                 | 7/16-20                    | 17       | 4       | 30       | 15                            | <b>4G4MXS</b>        | <b>4G4MXSS</b>            | 315      | 315 |
| 6                 | 1/4   | 1/4-19                 | 7/16-20                    | 19       | 4       | 35       | 42                            | <b>4-4G4MXS</b>      | <b>4-4G4MXSS</b>          | 400      | 350 |
| 8                 | 5/16  | 1/8-28                 | 1/2-20                     | 17       | 6       | 30       | 22                            | <b>5G4MXS</b>        | <b>5G4MXSS</b>            | 315      | 315 |
| 8                 | 5/16  | 1/4-19                 | 1/2-20                     | 19       | 6       | 35       | 40                            | <b>5-4G4MXS</b>      | <b>5-4G4MXSS</b>          | 400      | 350 |
| 10                | 3/8   | 1/4-19                 | 9/16-18                    | 19       | 8       | 36       | 40                            | <b>6G4MXS</b>        | <b>6G4MXSS</b>            | 400      | 350 |
| 10                | 3/8   | 3/8-19                 | 9/16-18                    | 22       | 8       | 37       | 50                            | <b>6-6G4MXS</b>      | <b>6-6G4MXSS</b>          | 350      | 350 |
| 12                | 1/2   | 3/8-19                 | 3/4-16                     | 22       | 10      | 40       | 64                            | <b>8G4MXS</b>        | <b>8G4MXSS</b>            | 350      | 350 |
| 12                | 1/2   | 1/2-14                 | 3/4-16                     | 30       | 10      | 46       | 116                           | <b>8-8G4MXS</b>      | <b>8-8G4MXSS</b>          | 400      | 350 |
| 14, 15, 16        | 5/8   | 1/2-14                 | 7/8-14                     | 30       | 12      | 48       | 121                           | <b>10G4MXS</b>       | <b>10G4MXSS</b>           | 350      | 350 |
| 18, 20            | 3/4   | 3/4-14                 | 1 1/16-12                  | 36       | 16      | 52       | 188                           | <b>12G4MXS</b>       | <b>12G4MXSS</b>           | 315      | 315 |
| 25                | 1     | 1 1/4                  | 1 5/16-12                  | 46       | 22      | 60       | 340                           | <b>16G4MXS</b>       | <b>16G4MXSS</b>           | 280      | 280 |
| 28, 30, 32        | 1 1/4 | 1 1/4-11               | 1 5/8-12                   | 50       | 28      | 63       | 438                           | <b>20G4MXS</b>       | <b>20G4MXSS</b>           | 210      | 210 |
| 35, 38            | 1 1/2 | 1 1/2-11               | 1 7/8-12                   | 55       | 33      | 67       | 526                           | <b>24G4MXS</b>       | <b>24G4MXSS</b>           | 140      | 140 |

Les produits sont conformes à notre gamme standard de livraison.

Les versions métriques et pouces peuvent avoir des 6 pans de dimension différente.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Les pressions nominales (PN) peuvent différer selon la matière: acier (S) et inox (SS).

