



FF Femelle tournant Metru-Lok



XXXXX-XX-XX Référence 	D. Int. du tuyau				Filetage métrique	D. Ext. du tube mm	A mm	B mm	W mm
	DN	pouce	module	mm					
3FF82-6-4B	6	1/4	-4	6,3	M10x1	6	36	16	14
3FF82-8-4B	6	1/4	-4	6,3	M12x1	8	31	12	14
3FF82-10-6B	10	3/8	-6	9,5	M14x1	10	35	12	17
3FF82-12-6B	10	3/8	-6	9,5	M16x1	12	35	12	19
3FF82-14-8B	12	1/2	-8	12,7	M18x1	14	38	12	22
3FF82-16-8B	12	1/2	-8	12,7	M22x1,5	16	38	12	27
3FF82-18-10B	16	5/8	-10	15,9	M24x1,5	18	51	15	27
3FF82-22-12B	20	3/4	-12	19,1	M28x1,5	22	51	15	32

AF Mâle gaz cylindrique BSP – avec joint torique



XXXXX-XX-XX Référence 	D. Int. du tuyau				Filetage BSP	A mm	B mm	W mm
	DN	pouce	module	mm				
3AF82-2-4B	6	1/4	-4	6,3	1/8x28	34	15	17
3AF82-4-4B	6	1/4	-4	6,3	1/4x19	39	20	19
3AF82-4-6B	10	3/8	-6	9,5	1/4x19	43	20	19
3AF82-6-6B	10	3/8	-6	9,5	3/8x19	46	23	22
3AF82-6-8B	12	1/2	-8	12,7	3/8x19	49	22	22
3AF82-8-8B	12	1/2	-8	12,7	1/2x14	53	26	27
3AF82-8-10B	16	5/8	-10	15,9	1/2x14	63	26	27

Aussi disponible en acier inoxydable. Voir catalogue 4400.1

Série d'embouts compatible avec les tuyaux:

B: Laiton; **K:** Sans collerette plastique; **SM:** 6 pans métrique

 801 804 821FR 830M 831 836 837BM 837PU 838M